



Value-added distributer and supplier of technology solutions

ThinBox620: Powered by Intel CPU, The ThinBox620 is designed to support CPU-intensive and graphic demanding applications delivering

	SPECI	FICATIONS
System	Processor	Intel Quad Core 1.5Ghz
	Available operating system	W10 IOT/TOS
	VDI/HSD support	Citrix Receiver / VMWare View Client / RDP Client
	Management	CDMS
Memory	RAM (DDR4)	4GB (Up to 16GB)
	Storage (SSD)	64GB (Up to 256GB)
Display	Port	DVI-I x 1 (DVI-to-VGA adapter included) , DP x 1,
	Resolution	DVI-D Up to 1920 x 1200@60Hz / DP up to 4096 x 2160@60Hz
	Color depth	Up to 32bits true color
	Dual display	Supported
	Triple Display	Supported
Network	LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
I/O Peripheral Interface	USB 2.0	Rear: 4 x USB 2.0
	USB 3.0	Front: 1 x USB 3.0, Rear: 1x USB 3.0
Audio	Ports	Front: Line-out x 1, Mic-in x 1, (1/8-inch mini jack)
Dimension	Device	131mm x 31.5mm x 167mm
	Packaging	488mm x 256mm x 108mm
	Net weight	0.55 kg
Power	Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 12V/3A DC
	Power consumption	< 10w
Mounting	VESA bracket	VESA mounting kit included
	Kensington lock	Built-in Kensington security slot Fan-less convection 0°C to 40°C
Environment	Cooling	Fan-less convection
Environment		
Environment	Operation temperature	0°C to 40°C



